



ROMPOX® - UNIVERSAL SEALANT

Sealant to repel water and dirt

ROMPOX® - UNIVERSAL SEALANT is a dirt- and water-repellent impregnation for all absorbent tiles and slab coverings in interior and exterior areas. It prevents the penetration of moisture into the stone surface (hydrophobisation) and at the same time ensures water vapour diffusion from the inside of the stone. The impregnation has a water-repellent effect without sealing the surface. Thanks to the high UV resistance of ROMPOX® - UNIVERSAL SEALANT, it is particularly suitable for outdoor use.

Properties

- No discolouration of the surface
- Very good depth effect on porous tiles
- Quick and easy application
- UV-resistant

Uncoloured

ROMPOX® - UNIVERSAL SEALANT

Sealant to repel water and dirt

APPLICATION

Construction site requirements: The ideal application temperature is 10 °C up to 25 °C. Do not use ROMPOX® - UNIVERSAL SEALANT in direct sunlight. Test ROMPOX® - UNIVERSAL SEALANT before use on an inconspicuous area. Avoid splashes onto adjacent, solvent sensitive surfaces (painted surfaces, plastics etc.) With stones laid onto a mortar bed, the foundation must be completely hardened and dry (usually after 4–8 weeks), because ROMPOX® - UNIVERSAL SEALANT may otherwise dry unevenly, which leads to a patchy appearance.

Preparation: Clean the surface thoroughly and let it dry completely. Adjacent surfaces must be covered or taped off. For the previous cleaning we recommend ROMPOX® - BASIC CLEANER EXTRA. See separate product information. Before every application, a small sample surface should be treated in order to see visually whether it appeals.

Application: When using indoors, turn off floor heating and ensure sufficient ventilation. Undiluted ROMPOX® - UNIVERSAL SEALANT is applied generously and uniformly using a brush or a roller onto the stone surface. For particularly porous stone surfaces, repeat the process after about 1 hour. For less porous surfaces, do not leave ROMPOX® - UNIVERSAL SEALANT on the surface, but rather before it dries, rub it off using a clean cloth or sponge. Drying time: 1 hour at 20 °C ambient temperature.

Subsequent treatment: The freshly treated surface should be protected from rain for 12 hours. The rain cover must not be placed directly onto the surface, to ensure air circulation. When treating stones and slabs indoors, windows must be open to ensure good ventilation. Tools can be cleaned after application with commercially available solvent.

Important notes: Wait at least 7 days between jointing with synthetic resin paving mortar and using ROMPOX® - UNIVERSAL SEALANT, in order to avoid interactions. **Non porous stone surfaces can not be treated.**

Storage life: 36 months

Ingredients: >30 % aliphatic hydrocarbons, <1 % hydrophobing agent, auxiliaries

Consumption: approx. 10 m²/Liter, depending on type of covering



GENERAL NOTES

Filler materials

All filler materials are natural products which are subject to natural colour deviations.

Water permeability coefficient

Water permeable according to „Leaflet on surfaces that allow for seepage“ (MVV), Issue 2013.

General notes

The information printed in this brochure is based on experiential values and the current levels of knowledge in science and practice, however they are not binding and have no legal force. All previous information becomes invalid with the issue of this brochure. Images similar. Effective June 2022. We reserve the right to make changes.

Follow us:



ROMEX® GmbH

Industriepark Kottenforst
Mühlgrabenstraße 21
53340 Meckenheim
+49 (0) 2225 70954-20
www.romex-ag.de

